


□ CUBUS RECESSED



ARCHILIGHT





DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SCV130	595x60x62	9	1340/1420
SCV250	595x60x62	12	1860/1960
SCV195	850x60x62	12	2010/2130
SCV375	850x60x62	18	2790/2940
SCV260	1135x60x62	16	2680/2840
SCV500	1135x60x62	24	3720/3920
SCV325	1415x60x62	21	3350/3550
SCV625	1415x60x62	31	4650/4900
SCV2x195	1700x60x62	26	4020/4260
SCV2x375	1700x60x62	37	5580/5880
SCV2x230	1980x60x62	29	4690/4970
SCV2x440	1980x60x62	43	6510/6860
SCV2x260	2265x60x62	33	5360/5680
SCV2x500	2265x60x62	49	7440/7840
SCV2x325	2825x60x62	41	6700/7100
SCV2x625	2825x60x62	61	9300/9800

## INSTALLATION

Recessed version

## CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block Luminaires for dimming are delivered with 5-pole terminal block

## MATERIAL

The body of the luminaire is extruded aluminium, powder coated finish

## LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

## DIFFUSER

PMMA OPAL  
PRISMATIC

## LIGHT DISTRIBUTION

Direct symmetrical


## EMERGENCY LIGHTING

A unit with integrated emergency is an option

## DIMMING

Most models can be delivered with ballast for dimming (TOUCHDIM, DALI)

## ACCESSORIES



63 mm

## COLOR TEMPERATURE

3000K /3K  
4000K /4K

## OPTIC

PMMA OPAL /--  
PRISMATIC /P

## DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI  
WIRELESS /WRS

## COLORS

	WHITE	/WH
	BLACK	/BL
	SILVER	/SI
	ANTRACIT	/AT
	GOLD	/GL
	BRONZE	/BR