


□ DUAL WALL





DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SDW130	595x49x85	9	1340/1420
SDW250	595x49x85	12	1860/1960
SDW195	850x49x85	12	2010/2130
SDW375	850x49x85	18	2790/2940
SDW260	1135x49x85	16	2680/2840
SDW500	1135x49x85	24	3720/3920
SDW325	1415x49x85	21	3350/3550
SDW625	1415x49x85	31	4650/4900
SDW2x195	1700x49x85	26	4020/4260
SDW2x375	1700x49x85	37	5580/5880
SDW2x230	1980x49x85	29	4690/4970
SDW2x440	1980x49x85	43	6510/6860
SDW2x260	2265x49x85	33	5360/5680
SDW2x500	2265x49x85	49	7440/7840
SDW2x325	2825x49x85	41	6700/7100
SDW2x625	2825x49x85	61	9300/9800

DIRECT/ INDIRECT CODE	(mm)	W	Lm from 3000K/4000K
SDW130/DI	595x49x85	17	2680/2840
SDW250/DI	595x49x85	25	3720/3920
SDW195/DI	850x49x85	25	4020/4260
SDW375/DI	850x49x85	37	5580/5880
SDW260/DI	1135x49x85	33	5360/5680
SDW500/DI	1135x49x85	49	7440/7840
SDW325/DI	1415x49x85	41	6700/7100
SDW625/DI	1415x49x85	61	9300/9800
SDW2x195/DI	1700x49x85	52	8040/8520
SDW2x375/DI	1700x49x85	74	11160/11760
SDW2x230/DI	1980x49x85	58	9380/9940
SDW2x440/DI	1980x49x85	86	13020/13720
SDW2x260/DI	2265x49x85	66	10720/11360
SDW2x500/DI	2265x49x85	98	14880/15680
SDW2x325/DI	2825x49x85	83	13400/14200
SDW2x625/DI	2825x49x85	123	18600/19600



INSTALLATION

Wall version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block. Luminaires for dimming are delivered with 5-pole terminal block.

MATERIAL

The body of the luminaire is extruded aluminium, eloxed or powder coated finish.

LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

DIFFUSER

PMMA OPAL
PRISMATIC

LIGHT DISTRIBUTION

Direct symmetrical
Direct symmetrical / active indirect symmetrical

EMERGENCY LIGHTING

A unit with integrated emergency is an option.

DIMMING

Most models can be delivered with ballast for dimming (TOUCHDIM, DALI)

COLOR TEMPERATURE

3000K /3K
4000K /4K

OPTIC

PMMA OPAL /--
PRISMATIC /P

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI
WIRELESS /WRS

COLORS

	ELOX	/...
	WHITE	/WH
	BLACK	/BL
	SILVER	/SI
	ANTRACIT	/AT
	GOLD	/GL
	BRONZE	/BR

ACCESSORIES

49
85
SDPKK
END CAP
2PCS