


□ LUCID SUSPENDED, CEILING, WALL



EXAMPLE OF ASSEMBLY LUCID SYSTEM

1. SUSPENDED / CEILING-WALL



INSTALLATION

Suspended, ceiling, wall or recessed version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block, through wired
Luminaires for dimming are delivered with 5-pole terminal block, through wired

MATERIAL

The body of the luminaire is extruded aluminium, eloxed finish

LIGHT SOURCE

LED Tridonic or TCI, min. 125Lm/W, 3000K or 4000K

DIFFUSER

PMMA OPAL
PRISMATIC

LIGHT DISTRIBUTION

Direct and sidewalls

EMERGENCY LIGHTING

A unit with integrated emergency is an option

DIMMING

All models can be delivered with ballast for dimming (TOUCHDIM, DALI)

70



57



CODE SUSPENDED	CODE CEILING / WALL	L (MM) BY PSE	L (mm) by PPE	W	Lm from 3000K/4000K
SLS130/PSE	SLC130/PSE	580x57x70	590x57x70	8	1500/1580
SLS250/PSE	SLC250/PSE	580x57x70	590x57x70	14	2340/2450
SLS195/PSE	SLC195/PSE	850x57x70	860x57x70	13	2250/2370
SLS375/PSE	SLC375/PSE	850x57x70	860x57x70	21	3510/3690
SLS260/PSE	SLC260/PSE	1135x57x70	1145x57x70	16	3000/3160
SLS500/PSE	SLC500/PSE	1135x57x70	1145x57x70	28	4680/4900
SLS325/PSE	SLC325/PSE	1415x57x70	1425x57x70	21	3750/3950
SLS625/PSE	SLC625/PSE	1415x57x70	1425x57x70	35	5850/6150
SLS2x195/PSE	SLC2x195/PSE	1700x57x70	1710x57x70	26	4500/4740
SLS2x375/PSE	SLC2x375/PSE	1700x57x70	1710x57x70	42	700/7380
SLS2x230/PSE	SLC2x230/PSE	1990x57x70	2000x57x70	29	5250/5530
SLS2x440/PSE	SLC2x440/PSE	1990x57x70	2000x57x70	49	8190/8610
SLS2x260/PSE	SLC2x260/PSE	2265x57x70	2275x57x70	32	6000/6320
SLS2x500/PSE	SLC2x500/PSE	2265x57x70	2275x57x70	56	9360/9800
SLS2x325/PSE	SLC2x325/PSE	2825x57x70	2835x57x70	42	7500/7900
SLS2x625/PSE	SLC2x625/PSE	2825x57x70	2835x57x70	70	11700/12300

COLOR TEMPERATURE

3000K /3K
4000K /4K

OPTIC

PMMA OPAL /--

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI see page 223
WIRELESS /WRS see page 223

COLOR TEMPERATURE

3000K /3K
4000K /4K

OPTIC

PMMA OPAL /--

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI
WIRELESS /WRS

COLORS

ELOX /..

COLOR TEMPERATURE

3000K /3K
4000K /4K

OPTIC

PMMA OPAL /--
PRISMATIC /P

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI
WIRELESS /WRS

ACCESSORIES

